

SOMETHING IS WRONG?


THE USER FRIENDLY STRATUS EMS CLOUD-BASED MONITORING SYSTEM GIVES PEACE OF MIND KNOWING EVERYTHING IS OKAY WHILE YOU'RE AWAY.

STRATUS EM

CONVENIENT WEB-BASED MANAGEMENT

STRATUS EMS

Integrate Remote Monitoring into your Data Center



Facility managers and personnel must constantly monitor environmental and equipment status, especially after hours. The Stratus EMS can provide peace of mind that everything is under control while you're away.

Features

- Cloud Based Monitoring
 & Data Acquisition
- Monitors in real time
- Instant Alarm Processing
 & Delivery
- Datalogs, Graphs, and Logs Alarm Events
- Create, Print & export Reports from the Dashboard
- 64 Modbus Sensor
 Capability
- 12 Universal Digital or Analog Hardwired Zones
- Cellular or Ethernet
 Connection Options

ENVIRONMENTAL MONITORING FOR THE MOBILE AGE

| 1:52 | ari S | |
|-------------------------|--------------------|-----|
| Kert Back Device | Device Detail Sett | |
| Modbus Zones | | |
| Zones Power | On | 0 |
| Battery | 100% | (1) |
| | | (j) |
| Lithium Battery | 100 % | 1 |
| Boiler Room Temp | 67.5F | (j) |
| Chiller Pump | Running | (i) |
| Chiller Flow | 10.185 gpm | (1) |
| Air Handler Pressure | -0.010 inWC | (i) |
| ChillerWater DO | 0.817 mg/l | (i) |
| Chiller Water Supply Te | mp 67.3F | 1 |
| Blower Health/Vibration | 37.504 mm/s | (j) |
| Heat Pump Amperage | 50.006 Amps | (i) |
| PDU 1 Amps | 6.502 amps | (i) |
| PDU 2 Amps | 10.002 amps | (i) |
| Leak Detection System | Rows 1 OK | (i) |
| Leak Detection System | Rows 4 OK | (i) |

- View your status in real time from a mobile app or any web browser
- Free unlimited e-mail and e-mail-to-text alerts. Add unlimited voice and text notifications with a low cost optional premium subscription.
- Monitor up to 64 Modbus Registers and connect up to 12 digital or analog sensors to monitor 4-20mA, NO/NC, Runtimes, Thermistors, and Pulse Counting.
- Easily manage multiple devices from one account. Alerts can be set to notify specific personnel for each location.
- Internal battery backup will continue to run the system in the event of a power failure.



HOW IT WORKS



The Stratus EMS integrates with a BMS or other equipment via RS485 or TCP to monitor up to 64 registers. Additionally, connect up to 12 digital or analog sensors to monitor temperature, humidity, and more.



Create a free account on sensaphone. net, register your Stratus EMS, and begin programming. You can set limits on your sensors and should they be exceeded, the Stratus EMS will call, text or e-mail any programmed users.

Check on your application by using the app or login to your account to see real time status. Check that temperature, humidity, security and more are okay while you're away.

Learn More: www.sensaphone.com/ Stratus

Distributed By:

SENSAPHONE® 901 TRYENS ROAD ASTON, PA 19014

PH: 877-838-0125 F: 610-558-0222

WWW.SENSAPHONE.COM