

SENSAPHONE[®]

REMOTE MONITORING SOLUTIONS



Sensaphone WSG30

Expand the Capabilities of your Sensaphone



Room Temperature Sensor

Includes a built-in radio transmitter and temperature element for monitoring temperature wherever the device is installed. Designed to monitor air temperatures from 32° to 122°F. Can be

battery powered or use a plug-in power supply.

WSG Wireless Room Temperature Sensor FGD-WSG30-TMP



Dry Contact Interface

Includes a built-in radio transmitter and input terminals for connecting to any normally-open or normally closed output.

WSG Wireless Room Temperature Sensor FGD-WSG30-DRY



Temperature Sensor with External Probe

Includes a built-in radio transmitter and a remote temperature probe so that temperature measurements can be made in a refrigerator, freezer or other harsh

environments. Designed to monitor temperatures from -20° to 122°F at a location away from the wireless sensor. Can be battery powered or use a plug-in power supply.

WSG Wireless Room Temperature Sensor FGD-WSG30-TEX



Power Failure Sensor

Includes a built-in radio transmitter, two AA alkaline batteries and a wall plug in power supply. The sensor will detect a loss of power at the outlet where the power supply is attached.

WSG Wireless Room Temperature Sensor FGD-WSG30-PWR



Ultra Low Temperature Sensor with External Probe

Includes a built-in radio transmitter and a remote temperature probe so that temperature measurements can be made in a refrigerator, freezer or other harsh

environments. Designed to monitor temperatures from -122° to 122°F at a location away from the wireless sensor. Can be battery powered or use a plug-in power supply.

WSG Wireless Room Temperature Sensor FGD-WSG30-TEX85



4-20mA Interface

Includes a built-in radio transmitter, 4-20mA input and a 24V loop power supply. The sensor can be used to monitor the output of any 4-20mA transducer.

WSG Wireless Room Temperature Sensor FGD-WSG30-4-20



Spot Water Detection Sensor

Includes a built-in radio transmitter and water sensing probes for monitoring for the presence of water at a particular location.

WSG Wireless Spot Water Detection Sensor FGD-WSG30-SPOT



Humidity Sensor

Includes a built-in radio transmitter and humidity sensor element for monitoring humidity wherever the device is installed.

WSG Wireless Room Temperature Sensor FGD-WSG30-HUM



Zone Water Detection Sensor

Includes a built-in radio transmitter and 10 feet of water sensing cable for monitoring for the presence of water in a particular area. The monitored area can be extended by attaching up to 9 additional lengths of Water Rope to the end of the included Water Rope.

WSG Wireless Zone Water Detection Sensor FGD-WSG30-ZONE



Power Supply for WSG30 Wireless Sensors

Used for powering WSG30 Wireless
sensors.

WSG Wireless Room Temperature SensorXFR-0041


A complete accessory specification sheet is available for all sensors and accessories. A complete parts list is available upon request or at www.sensaphone.com. All specifications subject to change.

SENSAPHONE®
901 TRYENS ROAD
ASTON, PA 19014

PH: 877-373-2700
F: 610-558-0222

WWW.SENSAPHONE.COM

Distributed By:



LIT-xxxx © SENSAPHONE 11/2013