SENSAPHONE® REMOTE MONITORING SOLUTIONS

FGD-0056

Zone Water Detection Sensor



The Zone Water Detection Sensor senses the presence of water via the attached WaterRope. It can be used with all models. The sensor is a normally closed device. It operates on two (2) AA batteries (installed).

PACKAGE CONTENTS

- (1) FGD-0056 Zone Water Detector
- (1) 10' of WaterRope
- (5) Adhesive cable clamps
- (2) Plastic drywall anchors
- (2) #6 Metal tapping screws
- (4) Rubber feet

MOUNTING INSTRUCTIONS

Mount the Zone Water Detection Sensor on a wall or other surface where it will not be immersed, but near enough to the surface being monitored to make the best use of the WaterRope. Plug in the WaterRope before attaching cable clamps to secure it to the monitored surface.

WIRING INSTRUCTIONS

- 1. Connect two wires to the two screw terminals on the detector.
- Connect one of the wires to a zone or input terminal on your Sensaphone. Connect the other to the corresponding ground or common terminal. Consult your specific Sensaphone's manual to determine the appropriate inputs for use with the Zone Water Detector.
- 3. Configure your input normality as normally closed.
 - For models 400, 800, 1400, 1800: Press Set, then Configure to set normality.
 - For Sensaphone 2000, WEB600, SAT4D, Cell682, SCADA 3000, and Express II: Program the input type as normally closed.
 - Consult your Sensaphone owner's manual for further instructions.
- 4. Test the sensor by moistening a paper towel and wrapping it around any portion of the WaterRope.

EXTENDING THE MONITORED AREA

The size of the monitored area can be extended by attaching additional lengths of WaterRope (FGD-0063) to the end of the included WaterRope. You can connect up to ten (10) lengths of WaterRope (100') to one Zone Water Detector.

SPECIFICATIONS:

Normality: Normally closed

Dimensions: 5.48" x 3.30" x 1.35" (Mounting holes are 4.98" apart)

Number per input: 5 (wired in series)

For technical support, call 877-373-2700.

	et is available for all sensors and accessors om. All specifications subject to change.	es. A complete parts list is available
SENSAPHONE® 901 TRYENS ROAD ASTON, PA 19014	Distrib	uted By:
PH: 877-373-2700 F: 610-558-0222		3 ⊚ SENSAP

WWW.SENSAPHONE.COM